## **Forklift Differential**

Differentials for Forklifts - A differential is a mechanical device which can transmit rotation and torque through three shafts, often but not at all times employing gears. It usually operates in two ways; in cars, it provides two outputs and receives one input. The other way a differential functions is to combine two inputs to create an output that is the sum, average or difference of the inputs. In wheeled vehicles, the differential enables all tires to rotate at different speeds while providing equal torque to all of them.

The differential is intended to power the wheels with equal torque while also allowing them to rotate at different speeds. If traveling round corners, the wheels of the cars will rotate at various speeds. Several vehicles such as karts work without utilizing a differential and utilize an axle in its place. If these vehicles are turning corners, both driving wheels are forced to rotate at the identical speed, usually on a common axle which is powered by a simple chain-drive mechanism. The inner wheel has to travel a shorter distance than the outer wheel when cornering. Without utilizing a differential, the consequence is the outer wheel dragging and or the inner wheel spinning. This puts strain on drive train, causing unpredictable handling, difficult driving and damage to the tires and the roads.

The amount of traction necessary in order to move whatever automobile would depend upon the load at that moment. Other contributing elements consist of drag, momentum and gradient of the road. One of the less desirable side effects of a traditional differential is that it could limit grip under less than perfect situation.

The torque supplied to each and every wheel is a product of the transmission, drive axles and engine applying a twisting force against the resistance of the traction at that specific wheel. The drive train can usually supply as much torque as needed except if the load is very high. The limiting element is usually the traction under every wheel. Traction can be defined as the amount of torque that could be produced between the road surface and the tire, before the wheel starts to slip. The automobile will be propelled in the planned direction if the torque used to the drive wheels does not exceed the limit of traction. If the torque applied to each wheel does exceed the traction limit then the wheels would spin continuously.